BOURT ISSUE: 2021

EXQUISITE
DESIGNS
CRAFTED FOR
YOUR HOME

WOOD GRAIN
FABRIC
SOLID



HOME THAT
SHOWCASE YOUR
LIFESTYLE

The exquisite range has been designed keeping the refined choices and lifestyle of discerning customers.



EXQUISITE WOOD GRAINS

Naturally occurring wood grain designs of Greenpanel's Pre-laminated MDF range of Wood Grain laminates. Brings luxury, class, and elegance to your interiors. Creating an awe-inspiring impression, that will last forever.















Rich walnut


0766



Desert Walnut 1122





















Rosa Walnut 1133

















GORGEOUS FABRIC FOR THAT ELEGANT LOOK

With the fine texture of the fabric, these stylish Pre-laminated MDF add royalty to your interior. Giving your living spaces a stunning makeover.





Chambray Grey 4047






White 0101

COLOUR EMOTION


Greenpanel's exquisite range of vivid solid coloured Pre-laminated MDF is selected carefully to add happiness and brightness to your interiors. Accentuating your desire for a tastefully crafted bright space, that brings a smile to your face.

Wool 0107



Gothic Grey 0210


Everest White 0117



Silver Grey 0270

Warm White 0118





lvory 0121





TECHNICAL SPECIFICATIONS

S.NO.	TEOT		Technical Specifications				
4	TEST	UNIT	PRE-LAMINATED MDF BOARD				
			EXTERIOR	INTERIOR			
1	Density	Kg/m³	600-900	600-900			
2	Density variation (Max)	%	± 10	± 10			
3	Moisture content	%	5-10	5-10			
4	Variation from mean moisture content (Max)	%	± 3	± 3			
5	Thickness swelling in 2 hrs (Max)	%	4	7			
6	Modulus of rupture (Min)	N/mm²					
	a. Upto 20 mm thickness (Average)		22-27	18-23			
	b. Above 20 mm thickness (Average)		15-22	15-18			
7	Modulus of elasticity (Min)	N/mm²					
	a. Upto 20 mm thickness (Average)		2300-2800	2100-2700			
	b. Above 20 mm thickness (Average)		1900-2300	1700-2100			
8	Internal bond strength (Min)	N/mm²					
	a. Upto 20 mm thickness		0.60-0.70	0.55-0.65			
	b. Above 20 mm thickness		0.50-0.60	0.50-0.55			
9	Internal bond strength (Min)	N/mm²					
	a. After cyclic test		0.10-0.35	N/A**			
	b. After AWR*		0.10-0.20	N/A**			
10	Screw withdrawal strength (Min)	N					
	a. Face		1250	1250			
	b. Edge (>12.0mm)		850	700			
11	Surface abrasion resistance (Min)						
	a. Type-I		1000	1000			
	b. Type-II	Revolutions	450	450			
	c. Type-III		250	250			
	d. Type-IV		75	75			
12	Resistance to steam/water vapours	-	No blister, delamination or change in surface finish				
13	Resistance to crack	-	No sign of crack or delamination				
14	Resistance to stain	-	No stain on the specimen after cleaning with water solvent or detergent				
15	Resistance to cigarette burn	-	No mark or stain on the specimen after cleaning with water or solvent				
16	Formaldehyde content (Fc)	mg/100 g for oven dry board	Formaldehyde class E1: Fc ≤ 8 Formaldehyde class E2: 8 < Fc ≤30				

AWR* = Accelerated Water Resistance N/A** = Not Applicable



Size

2.44m x 1.22m

Uttarakhand Plant

Caters to Delhi, Haryana, UP., Uttarakhand, J&K, HP., Punjab, Chandigarh, Rajasthan, Gujarat, Bihar, Jharkhand, West Bengal & North East

Thickness

Interior Grade: 4.6mm, 5.5mm, 7mm, 7.5mm, 9.75mm, 11mm, 14.5mm, 16.5mm, 17mm, 18mm & 25mm

Exterior Grade: 5.5mm, 7.5mm, 11mm, 16.5mm, 17mm, 25mm

Club Grade: 5.5mm, 7.5mm, 11mm, 16mm, 16.75mm & 18mm

Andhra Pradesh Plant

Caters to Andhra Pradesh, Karnataka, Tamil Nadu, Kerala, Odisha, Madhya Pradesh, Chhattisgarh & Maharashtra

Thickness

Interior Grade: 5.5mm, 7mm, 7.3mm, 11mm, 12mm, 17mm, 18mm, 25mm & 30mm

Exterior Grade: 5.5mm, 7.5mm, 11mm, 12mm, 17mm, 18mm, 25mm & 30 mm

Club Grade: 5.5mm, 7.5mm, 11mm, 16mm, 16.7mm & 18mm

Ecolite Grade: 10mm, 14.5mm & 16.7mm

MMR: 16.7mm

Advantages of Greenpanel **Pre-laminated MDF**



Level E1, E2







Exclusive Design Range




Imported Decor **Papers**



& Durable







Steam

Machinery

Resistant to Crack,



Scratch and Stains



Wide Distribution Network















ISO 9001: 2015, OHSA 18001: 2007, FSC, CARB, EPA and Green building certificates international standard Greenpanel Industries Limited environment is managed according to ISO 14001:2015 international environmental management systems standard. This embodies our commitment to pursuing a path of continual improvement in environmental management.

Greenpanel **Industries Limited**

3rd Floor, Plot No. 68, Sector 44, Gurugram 122003, Haryana. T+91-124-4784600 | F+91-124-4784699 | E info@greenpanel.com

Regd. Office: Makum Road, Tinsukia 786125, Assam

CIN: L20100AS2017PLC018272

Toll Free No. 1800-102-2999 (Mon - Fri except holidays 10 am-5 pm) www.greenpanel.com I Connect with us on