Technical Specifications				
S.NO.	TEST	UNIT	PRE-LAMINATED MDF BOARD VALUES***	
			EXTERIOR	INTERIOR
1	Density	Kg/m³	600-900	600-900
2	Density variation (Max)	%	± 10	± 10
3	Moisture content	%	5-10	5-10
4	Variation from mean moisture content (Max)	%	± 3	± 3
5	Thickness swelling in 24 hrs (Max) #	%	6-35	6-45
6	Modulus of rupture (Min)	N/mm²		
	a. Upto 20 mm thickness (Average)		22-27	18-23
	b. Above 20 mm thickness (Average)		15-22	15-18
7	Modulus of elasticity (Min)	N/mm²		
	a. Upto 20 mm thickness (Average)		2300-2800	2100-2800
	b. Above 20 mm thickness (Average)		1900-2300	1700-2100
8	Internal bond strength (Min)	N/mm²		
	a. Upto 20 mm thickness		0.60-0.70	0.55-0.65
	b. Above 20 mm thickness		0.50-0.60	0.50-0.55
9	Internal bond strength (Min)	N/mm²		
	a. After cyclic test		0.10-0.35	N/A**
	b. After AWR*		0.10-0.20	N/A**
10	Screw withdrawal strength (Min)	N		
	a. Face		1250	1250
	b. Edge (>12.0mm)		850	700
11	Surface abrasion resistance (Min)	No. of		
	a. Type-I		1000	1000
	b. Type-II	Revolutions	450	450
	c. Type-III		250	250
	d. Type-IV		75	75
12	Resistance to steam/water vapours	-	No blister, delamination or change in surface finish	
13	Resistance to crack	-	No sign of crack or delamination	
14	Resistance to stain	-	No stain on the specimen after cleaning with water solvent or detergent	
15	Resistance to cigarette burn	-	No mark or stain on the specimen after cleaning with water or solvent	
16	Formaldehyde content (F _C)	mg/100 g for oven dry board	Formaldehyde class E1: F _C ≤ 8 Formaldehyde class E2: 8 < F _C ≤30	
A 1 A / E	2* - Appalarated Water Registeres	# According	to the MDE's thickne	

vvK^ = Accelerated vva I/A** = Not Applicable

Size: 2440mm x 1220mm | 2440 mm x 1830mm

Thickness Available

Caters to Delhi, Haryana, U.P., Uttarakhand, J&K, H.P., Punjab, Chandigarh, Rajasthan, Gujarat, Bihar, Jharkhand, West Bengal & North East.

Interior Grade: 4.6mm, 5.5mm, 7mm, 7.3mm, 9.75mm,

Exterior Grade: 5.5mm, 7.5mm, 11mm, 16.5mm, 17mm,

HDWR: 5.5mm, 8mm, 11mm, 12mm, 16mm, 16.75mm, 18mm & 25mm

FRMDF: 12mm & 18mm

Caters to Andhra Pradesh, Karnataka, Tamil Nadu, Kerala,

Interior Grade: 5.5mm, 7mm, 7.3mm, 9.75mm, 11mm, 12mm, 14.5mm, 16mm, 16.5mm, 17mm, 18mm, 25mm & 30mm

Exterior Grade: 5.5mm, 7.5mm, 11mm, 12mm, 16.5mm,

FRMDF: 12mm & 18mm

FRMDF CLUB: 12mm & 18mm

Uttarakhand Plant

Thickness:

11mm, 14.5mm, 16.5mm, 17mm, 18mm, 25mm & 30mm

25mm & 30mm

FRMDF CLUB: 12mm & 18mm

Andhra Pradesh Plant

Odisha, Madhya Pradesh, Chhattisgarh & Maharashtra

Thickness:

17mm, 18mm, 25mm & 30mm

HDWR: 3.3mm, 5.5mm, 8mm, 12mm, 16mm, 16.75mm & 18mm & 25mm

MMR: 16.5mm

Advantages of Greenpanel Pre-laminated MDF





























































ISO 9001:2015, ISO 45001: 2018, FSC, CARB, EPA, CE and Green building certificates international standard. Greenpanel Industries Limited environment is managed according to ISO 14001:2015 international environmental management systems standard. This embodies our commitment to pursuing a path of continual improvement in environmental



Greenpanel Industries Limited


3rd Floor, Plot No. 68, Sector 44, Gurugram 122003, Haryana. T +91-124-4784600 (Monday to Friday except holidays 10 am to 5 pm) Regd. Office: Thapar House, 2nd Floor, 163, S.P. Mukherjee Road, Kolkata, West Bengal - 700026 Tel No : +91 33 4084 0600 CIN I 20100WB2017PI C265977

E info@greenpanel.com Toll Free No. 1800-102-2999

Connect with us or f y o in











Canyon White Oak 2503



Mellow Oak 2506








Caribbean Walnut 2011













Umber Oak 2507







English Wood 2203








Charcoal Wenge 2021







Persian Walnut Brown 2802







River Wood 2017
















Natural Mahogany 2004



Oxford Cherry 2016







Amazon Symphony 2202















New River Oak Dark 2501



Rosewood 2015



Planked Walnut 2803









WOOD GRAIN'S NATURAL ELEGANCE CAPTURED



Highland Pine 2001



Classic Bavarian Beech 2008



Persian Walnut Light 2801



Majestic Oak 2505



New River Oak Light 2502



EXPERIENCE THE AESTHETIC SPLENDOR OF WOOD GRAIN



Savanna Gold 2201



Planked Walnut 2803



Natural Wenge 2007



Latin Walnut 2809





Vintage Wenge 2002





ETERNAL STYLE INSPIRED BY FABRICS





Cambric Dark 2052

VIBRANT COLORS FOR A LASTING IMPRESSION



